

Assembly Instructions

Singles (Non-storage)

These bases are designed with a designated head end (divan cover border join).

- Fittings are located in the plastic bags attached to the underside of the base and include:
a) 6 castors/glides or 6 legs and castors/glides (shallow bases) b) 4 headboard bolts.
- Carefully tap each castor/glide into the metal sockets on the underside of the base (deep base) or screw the legs into the metal plates (shallow base).
- At the border join end of the base (headboard end), remove each 'Pierce Here' label in turn, carefully piercing the fabric with a sharp implement (e.g. a bradawl), where the head board socket can be felt. Be careful not to cause injury or damage during this operation. Insert a headboard bolt into the socket and tighten accordingly (4x per sprung edge base).

Singles (storage) (90cm width)

Singles Links (storage/non-storage) (90cm width - 180cm set)

- These bases are universal and can be positioned with either end acting as the head end.
- Fittings are located in the plastic bags attached to the underside of the base and include:
a) 6 castors/glides or 6 legs and castors/glides (shallow bases) b) 4 headboard bolts.
- Carefully tap each castor/glide into the metal sockets on the underside of the base (deep base) or screw the legs into the metal plates (shallow base).

Single (storage)

- Position the base where it is to be used.
- At the headboard end of the base, remove each 'Pierce Here' label in turn, carefully piercing the fabric with a sharp implement (e.g. a bradawl), where the headboard socket can be felt. Be careful not to cause injury or damage during this operation. Insert a headboard bolt into the socket and tighten accordingly (4x per sprung edge base).
- The 'Pierce Here' labels at the foot end of the base can be removed.

Single Links (storage/non-storage)

- Position the two base halves where they are to be used and bring them together. Ensure that the black unit connectors are facing each other.
- Standing to the end of the bed, lift the right hand base (approx. 100mm, and holding the left hand one in position, squeeze the bases together whilst lowering the right one, ensuring that the connectors locate.
- Repeat at the other end of the bed.
- At the headboard end of the base, remove each 'Pierce Here' label in turn, carefully piercing the fabric with a sharp implement (e.g. a bradawl), where the headboard socket can be felt. Be careful not to cause injury or damage during this operation. Insert a headboard bolt into the socket and tighten accordingly (4x per sprung edge base).
- The 'Pierce Here' labels at the foot end of the base can be removed.

IMPORTANT: Small/Standard Drawer bases (H and J type). These bases are not universal. Before proceeding, please ensure that you have been delivered a LEFT (H) and RIGHT (J) base. Headboard bolt fittings are always to be fitted to the small drawer end.

Doubles (105cm/120cm/135cm/150cm)

Your Sealy base is delivered in two halves.

Double base

- Fittings are located in the plastic bags attached to the underside of each base and include:
a) 4 castors/glides b) 2 headboard bolts.
- Position the two base halves where they are to be used and bring them together. Ensure the black unit connectors are facing each other.
- Standing to the side of the bed, lift the right hand base (approx. 100mm, and holding the left hand one in position, squeeze the bases together whilst lowering the right one ensuring that the connectors locate.
- Repeat at the other side of the bed.
- At the headboard end of the base, remove each 'Pierce Here' label in turn, carefully piercing the fabric with a sharp implement (e.g. a bradawl), where the headboard socket can be felt. Be careful not to cause injury or damage during this operation. Insert a headboard bolt into the socket and tighten accordingly (4x per sprung edge base).
- The 'Pierce Here' labels at the foot end of the base can be removed.

Shallow base (legs)

- Fittings are located in the plastic bags attached to the underside of each base and include:
a) 4 legs and castors/glides b) 1 linking plate c) 2 headboard bolts
- Position the two bases on their sides, with the metal corner plates at the outer corners of the base.
- To join the bases, insert a leg thread through the slot of one of the linking plates, and screw it loosely into one of the centre holes (identified by a 'Pierce Here' label).
- Screw a second leg into the opposing hole on the other base, link the 'hook' of the joining plate over it, and tighten both legs.
- Repeat for the other legs.
- Screw in the four corner legs and tighten.
- Lower the base into position for use.
- At the headboard end of the base, remove each 'Pierce Here' label in turn, carefully piercing the fabric with a sharp implement (e.g. a bradawl), where the headboard socket can be felt. Be careful not to cause injury or damage during this operation. Insert a headboard bolt into the socket and tighten accordingly (4x per sprung edge base).
- The 'Pierce Here' labels at the foot end of the base can be removed.

Zip & Link models

Zip & link sets have two mattresses zipped together in the middle, on the top and bottom surfaces. (Non-turn mattresses are zipped on the top side only). They can be used as two singles or one large king-size bed.

End Drawer Divans

Please note that the End Drawer contains the headboard bolts for use in the 'head end' base.

In the interest of safety, please keep the plastic packaging away from children and ensure any staples that have been used to fix packaging are carefully removed and disposed of.

Customer Advice

The protective corners used with this product are designed to with stand scuffing and provide edge protection so that you receive your product in the best possible condition. We recommend that you use scissors to carefully remove the tags. Please do not attempt to pull the tags through the fabric. Always use scissors with caution.

Care Instructions

Protecting your investment in healthy sleep.
Getting used to your bed.

Sealy beds have generous layers of luxurious upholstery cushioning the spring unit. These areas where body weight is concentrated will compress as the materials bed themselves down. This can give rise to 'body impressions' which are perfectly normal.

Most Sealy Posturepedic mattresses are now NON TURN. This means that they only require rotating from end to end, which we would recommend that you do at least twice a month during the first year of use, then once a month thereafter. This process will minimise natural settlement and extend the comfort life of your mattress.

UNDER NO CIRCUMSTANCES SHOULD THE NON-SLEEPING SIDE BE USED AS A SLEEP SURFACE

Only our Ortho Collection Mattresses and some models in the Classic range are double sided, and these should be turned over and rotated with the same frequency as the Non Turn models.



DO: ROTATE THE MATTRESS FREQUENTLY

... but only turn if the mattress is double sided.



DO: USE A MATTRESS PROTECTOR

Body moisture can cause dyes in mattress covering fabric to 'bleed' and mark bed linen. A quality mattress protector will prevent this and other problems of mattress soiling.



DO: AIR THE MATTRESS REGULARLY

This is particularly important when the packaging is first removed as it will help any 'newness' aroma to dissipate.



DON'T: ROLL OR BEND THE MATTRESS

The spring interior is encased in a steel frame that will distort if bent and could remain so permanently.



DON'T: BOUNCE OR SIT REPEATEDLY IN THE SAME AREA

This can reduce the lifespan of the mattress and place undue strain on the spring unit.



DON'T: USE DETERGENT OR CHEMICAL CLEANERS

Many of these products will rot both cloth and fabric. In the event of soiling, the mattress may be lightly sponged with a mild solution of soap and water. The mattress should then be aired in a warm environment.